

In re Appln. of Higginson
Application No. 10/664,320

CLAIM AMENDMENTS

1. (Original) An electronic device comprising:
a base;
a display;
a cursor control member including an elongate, slender, rigid housing, the cursor control member having an attachment element arranged at one end of the housing for detachably fixing the cursor control member to the base;
a port carried by the base for receiving the attachment element of the cursor control member, the port including a movable surface that moves in response to movement of the cursor control member when the cursor control member is engaged with the port, movement of the movable surface producing control signals for directing movement of a cursor in the display; and
a locking mechanism for securing the cursor control member to the port on the base so as to prevent unintentional withdrawal of the cursor control member from the port, the locking mechanism including a release mechanism operable to unlock the cursor control member from the port so that the cursor control member can be removed from the port.
2. (Original) The electronic device according to claim 1 wherein the port is arranged on an adapter that is releasably connectable to the base.
3. (Original) The electronic device according to claim 1 wherein the cursor control member includes a manually operable input mechanism that produces control signals when operated and the attachment element and port are configured so as to communicate those control signals to a processing unit in the base.
4. (Original) The electronic device according to claim 3 wherein the input mechanism comprises a button.

In re Appln. of Higginson
Application No. 10/664,320

5. (Original) The electronic device according to claim 3 wherein the input mechanism comprises a wheel.
6. (Original) The electronic device according to claim 3 wherein the input mechanism comprises a touch surface.
7. (Original) The electronic device according to claim 1 wherein the attachment element of the cursor control member and the port have complementary configurations such that the cursor control member cannot rotate about its longitudinal axis relative to the movable surface on the base when the cursor control member is engaged with the port.
8. (Original) The electronic device according to claim 1 wherein the attachment element of the cursor control member and the port have complementary guide surfaces which engage each other upon insertion of the cursor control member into the port and guide the attachment element of the cursor control member into position for engagement with the port.
9. (Original) The electronic device according to claim 1 wherein an end of the cursor control member has a stylus tip.
10. (Original) The electronic device according to claim 1 wherein the cursor control member has a memory and the port and the attachment element of the cursor control member are configured such that content stored in the memory of the cursor control member can be communicated to a processing unit in the base when the cursor control member is engaged with the port.
11. (Original) The electronic device according to claim 1 wherein the cursor control member has a memory and the port and attachment element of the cursor control

In re Appln. of Higginson
Application No. 10/664,320

member are configured such that the memory of the cursor control member is usable by a processing unit in the base when the cursor control member is engaged with the port.

12. (Original) The electronic device according to claim 1 wherein the cursor control member includes a power supply and the port and attachment element of the cursor control member are configured such that power produced by the power supply in the cursor control member is available to operate the processing unit in the base when the cursor control member is engaged with the port.

13. (Original) The electronic device according to claim 1 further including a storage slot on the base, the storage slot being configured to receive the cursor control member.

14. (Original) An electronic device comprising:

a base;

a display;

a cursor control member including an elongate, slender, rigid housing, the cursor control member having an attachment element arranged at one end of the housing for detachably fixing the cursor control member to the base;

a port carried by the base for receiving the attachment element of the cursor control member, the port including a movable surface that moves in response to movement of the cursor control member when the cursor control member is engaged with the port, movement of the movable surface producing control signals for directing movement of a cursor in the display; and

wherein the attachment element of the cursor control member and the port have complementary configurations such that the cursor control member cannot rotate about its longitudinal axis relative to the movable surface on the base when the cursor control member is engaged with the port.

In re Appln. of Higginson
Application No. 10/664,320

15. (Original) The electronic device according to claim 14 wherein the port is arranged on an adapter that is releasably connectable to the base.

16. (Original) The electronic device according to claim 14 wherein the cursor control member includes a manually operable input mechanism that produces control signals when operated and the attachment element and port are configured so as to communicate those control signals to a processing unit in the base.

17. (Original) The electronic device according to claim 16 wherein the input mechanism comprises a button.

18. (Original) The electronic device according to claim 16 wherein the input mechanism comprises a wheel.

19. (Original) The electronic device according to claim 16 wherein the input mechanism comprises a touch surface.

20. (Original) The electronic device according to claim 14 wherein the attachment element of the cursor control member and the port have complementary guide surfaces which engage each other upon insertion of the cursor control member into the port and guide the attachment element of the cursor control member into position for engagement with the port.

21. (Original) The electronic device according to claim 14 wherein an end of the cursor control member has a stylus tip.

22. (Original) The electronic device according to claim 14 wherein the cursor control member has a memory and the port and the attachment element of the cursor control member are configured such that content stored in the memory of the cursor

In re Appln. of Higginson
Application No. 10/664,320

control member can be communicated to a processing unit in the base when the cursor control member is engaged with the port.

23. (Original) The electronic device according to claim 14 wherein the cursor control member has a memory and the port and attachment element of the cursor control member are configured such that the memory of the cursor control member is usable by a processing unit in the base when the cursor control member is engaged with the port.

24. (Original) The electronic device according to claim 14 wherein the cursor control member includes a power supply and the port and attachment element of the cursor control member are configured such that power produced by the power supply in the cursor control member is available to operate the processing unit in the base when the cursor control member is engaged with the port.

25. (Original) The electronic device according to claim 14 further including a storage slot on the base, the storage slot being configured to receive the cursor control member.

26. (Original) An electronic device comprising:

a base;

a display;

a cursor control member including an elongate, slender, rigid housing, the cursor control member having an attachment element arranged at one end of the housing for detachably fixing the cursor control member to the base;

a port carried by the base for receiving the attachment element of the cursor control member, the port including a movable surface that moves in response to movement of the cursor control member when the cursor control member is engaged with the port, movement of the movable surface producing control signals for directing movement of a cursor in the display; and

In re Appln. of Higginson
Application No. 10/664,320

wherein the attachment element of the cursor control member and the port have complementary guide surfaces which engage each other upon insertion of the cursor control member into the port and guide the attachment element of the cursor control member into position for engagement with the port.

27. (Original) The electronic device according to claim 26 wherein the port is arranged on an adapter that is releasably connectable to the base.

28. (Original) The electronic device according to claim 26 wherein the cursor control member includes a manually operable input mechanism that produces control signals when operated and the attachment element and port are configured so as to communicate those control signals to a processing unit in the base.

29. (Original) The electronic device according to claim 28 wherein the input mechanism comprises a button.

30. (Original) The electronic device according to claim 28 wherein the input mechanism comprises a wheel.

31. (Original) The electronic device according to claim 28 wherein the input mechanism comprises a touch surface.

32. (Original) The electronic device according to claim 26 wherein an end of the cursor control member has a stylus tip.

33. (Original) The electronic device according to claim 26 wherein the cursor control member has a memory and the port and the attachment element of the cursor control member are configured such that content stored in the memory of the cursor control member can be communicated to a processing unit in the base when the cursor control member is engaged with the port.

In re Appln. of Higginson
Application No. 10/664,320

34. (Original) The electronic device according to claim 26 wherein the cursor control member has a memory and the port and attachment element of the cursor control member are configured such that the memory of the cursor control member is usable by a processing unit in the base when the cursor control member is engaged with the port.

35. (Original) The electronic device according to claim 26 wherein the cursor control member includes a power supply and the port and attachment element of the cursor control member are configured such that power produced by the power supply in the cursor control member is available to operate the processing unit in the base when the cursor control member is engaged with the port.

36. (Original) The electronic device according to claim 26 further including a storage slot on the base, the storage slot being configured to receive the cursor control member.

37. (Original) An electronic device comprising:

a base;

a display;

a cursor control member including an elongate, slender, rigid housing, the cursor control member having an attachment element arranged at one end of the housing for detachably fixing the cursor control member to the base;

a port carried by the base for receiving the attachment element of the cursor control member, the port being adapted to translate movement of the cursor control member into control signals for directing movement of a cursor in the display when the cursor control member is engaged with the port; and

wherein an end of the cursor control member has a stylus tip.

38. (Original) The electronic device according to claim 37 wherein the port is arranged on an adapter that is releasably connectable to the base.

In re Appln. of Higginson
Application No. 10/664,320

39. (Original) The electronic device according to claim 37 wherein the cursor control member includes a manually operable input mechanism that produces control signals when operated and the attachment element and port are configured so as to communicate those control signals to a processing unit in the base.

40. (Original) The electronic device according to claim 39 wherein the input mechanism comprises a button.

41. (Original) The electronic device according to claim 39 wherein the input mechanism comprises a wheel.

42. (Original) The electronic device according to claim 39 wherein the input mechanism comprises a touch surface.

43. (Original) The electronic device according to claim 37 wherein the cursor control member has a memory and the port and the attachment element of the cursor control member are configured such that content stored in the memory of the cursor control member can be communicated to a processing unit in the base when the cursor control member is engaged with the port.

44. (Original) The electronic device according to claim 37 wherein the cursor control member has a memory and the port and attachment element of the cursor control member are configured such that the memory of the cursor control member is usable by a processing unit in the base when the cursor control member is engaged with the port.

45. (Original) The electronic device according to claim 37 wherein the cursor control member includes a power supply and the port and attachment element of the cursor control member are configured such that power produced by the power supply in

In re Appln. of Higginson
Application No. 10/664,320

the cursor control member is available to operate the processing unit in the base when the cursor control member is engaged with the port.

46. (Original) The electronic device according to claim 37 further including a storage slot on the base, the storage slot being configured to receive the cursor control member.

47. (Previously Presented) An electronic device comprising:

a base;

a cursor control member including:

a housing,

an attachment element arranged at one end of the housing for detachably securing the cursor control member to the base, and

a memory; and

a port carried by the base for receiving the attachment element of the cursor control member, the port being adapted to translate movement of the cursor control member into control signals for directing movement of a cursor in a display when the cursor control member is engaged with the port and wherein the port and the attachment element of the cursor control member are configured such that content stored in the memory of the cursor control member can be communicated to a processing unit when the cursor control member is engaged with the port.

48. (Original) The electronic device according to claim 47 wherein the port is arranged on an adapter that is releasably connectable to the base.

49. (Previously Presented) The electronic device according to claim 47 wherein the cursor control member includes a manually operable input mechanism that produces control signals when operated and the attachment element and port are configured so as to communicate those control signals to a processing unit.

In re Appln. of Higginson
Application No. 10/664,320

50. (Original) The electronic device according to claim 49 wherein the input mechanism comprises a button.

51. (Original) The electronic device according to claim 49 wherein the input mechanism comprises a wheel.

52. (Original) The electronic device according to claim 49 wherein the input mechanism comprises a touch surface.

53. (Canceled)

54. (Original) The electronic device according to claim 47 wherein the cursor control member includes a power supply and the port and attachment element of the cursor control member are configured such that power produced by the power supply in the cursor control member is available to operate the processing unit in the base when the cursor control member is engaged with the port.

55. (Original) The electronic device according to claim 47 further including a storage slot on the base, the storage slot being configured to receive the cursor control member.

56. (Original) The electronic device according to claim 47 wherein the processing unit of the base produces a second control signal that controls movement of the cursor control member upon occurrence of a predetermined event when the cursor control member is engaged with the port.

In re Appln. of Higginson
Application No. 10/664,320

57. (Original) An electronic device comprising:

a base including a processing unit;

a display;

a cursor control member including a housing, the cursor control member having an attachment element arranged at one end of the housing for detachably securing the cursor control member to the base and a memory; and

a port carried by the base for receiving the attachment element of the cursor control member, the port including a movable surface that moves in response to movement of the cursor control member when the cursor control member is engaged with the port, movement of the movable surface producing control signals for directing movement of a cursor in the display and wherein the port and attachment element of the cursor control member are configured such that the memory of the cursor control member is usable by the processing unit in the base when the cursor control member is engaged with the port.

58. (Original) The electronic device according to claim 57 wherein the port is arranged on an adapter that is releasably connectable to the base.

59. (Original) The electronic device according to claim 57 wherein the cursor control member includes a manually operable input mechanism that produces control signals when operated and the attachment element and port are configured so as to communicate those control signals to a processing unit in the base.

60. (Original) The electronic device according to claim 59 wherein the input mechanism comprises a button.

61. (Original) The electronic device according to claim 59 wherein the input mechanism comprises a wheel.

In re Appln. of Higginson
Application No. 10/664,320

62. (Original) The electronic device according to claim 59 wherein the input mechanism comprises a touch surface.

63. (Original) The electronic device according to claim 57 wherein the cursor control member includes a power supply and the port and attachment element of the cursor control member are configured such that power produced by the power supply in the cursor control member is available to operate the processing unit in the base when the cursor control member is engaged with the port.

64. (Original) The electronic device according to claim 57 further including a storage slot on the base, the storage slot being configured to receive the cursor control member.

65. (Original) The electronic device according to claim 57 wherein the processing unit of the base produces a second control signal that controls movement of the cursor control member upon occurrence of a predetermined event when the cursor control member is engaged with the port.

In re Appln. of Higginson
Application No. 10/664,320

66. (Original) An electronic device comprising:

a base including a processing unit;

a display;

a cursor control member including a housing, the cursor control member having an attachment element arranged at one end of the housing for detachably securing the cursor control member to the base and a power supply; and

a port carried by the base for receiving the attachment element of the cursor control member, the port including a movable surface that moves in response to movement of the cursor control member when the cursor control member is engaged with the port, movement of the movable surface producing control signals for directing movement of a cursor in the display and wherein the port and attachment element of the cursor control member are configured such that power produced by the power supply in the cursor control member is available to operate the processing unit in the base when the cursor control member is engaged with the port.

67. (Original) The electronic device according to claim 66 wherein the port is arranged on an adapter that is releasably connectable to the base.

68. (Original) The electronic device according to claim 66 wherein the cursor control member includes a manually operable input mechanism that produces control signals when operated and the attachment element and port are configured so as to communicate those control signals to a processing unit in the base.

69. (Original) The electronic device according to claim 68 wherein the input mechanism comprises a button.

70. (Original) The electronic device according to claim 68 wherein the input mechanism comprises a wheel.

In re Appln. of Higginson
Application No. 10/664,320

71. (Original) The electronic device according to claim 68 wherein the input mechanism comprises a touch surface.

73. (Original) The electronic device according to claim 66 further including a storage slot on the base, the storage slot being configured to receive the cursor control member.

74. (Original) The electronic device according to claim 66 wherein the processing unit of the base produces a second control signal that controls movement of the cursor control member upon occurrence of a predetermined event when the cursor control member is engaged with the port.

In re Appln. of Higginson
Application No. 10/664,320

75. (Original) An electronic device comprising:

a base;

a display;

a cursor control member including a housing, the cursor control member having an attachment element arranged at one end of the housing for detachably securing the cursor control member to the base;

a port carried by the base for receiving the attachment element of the cursor control member, the port including a movable surface that moves in response to movement of the cursor control member when the cursor control member is engaged with the port, movement of the movable surface producing control signals for directing movement of a cursor in the display; and

a storage slot on the base, the storage slot being configured to receive the cursor control member.

~~75g. (Canceled) The electronic device according to claim 74 wherein the port is arranged on an adapter that is releasably connectable to the base.~~

76. (Currently Amended) The electronic device according to claim ~~74~~75 wherein the cursor control member includes a manually operable input mechanism that produces control signals when operated and the attachment element and port are configured so as to communicate those control signals to a processing unit in the base.

77. (Original) The electronic device according to claim 76 wherein the input mechanism comprises a button.

78. (Original) The electronic device according to claim 76 wherein the input mechanism comprises a wheel.

79. (Original) The electronic device according to claim 76 wherein the input mechanism comprises a touch surface.

In re Appln. of Higginson
Application No. 10/664,320

80. (Original) A cursor control member for an electronic device having a display and a port, the port including a movable surface that moves in response to movement of the cursor control member when the cursor control member is engaged with the port, movement of the movable surface producing control signals for directing movement of a cursor in the display, the cursor control member comprising an elongate, slender, rigid housing with an attachment element arranged at one end of the housing which can be received in the port and wherein an end of the housing is configured as a stylus tip.

81. (Original) A cursor control member for an electronic device having a display and a port, the port being adapted to translate movement of the cursor control member into control signals for directing movement of a cursor in the display of the electronic device when the cursor control member is engaged with the port, the cursor control member comprising an elongate, slender, rigid housing with an attachment element arranged at one end of the housing which can be received in the port and a memory, wherein the memory is accessible by the electronic device when the cursor control member is engaged in the port.

82. (Previously Presented) The electronic device of claim 47 wherein the electronic device supports wireless voice and data communications.

83. (Previously Presented) The electronic device of claim 47 wherein the electronic device supports mobile telephone communications.

84. (Previously Presented) The electronic device of claim 47 wherein the electronic device is a mobile phone.

85. (Previously Presented) The electronic device of claim 47 wherein the electronic device is a personal digital assistant (PDA).

In re Appln. of Higginson
Application No. 10/664,320

86. (Previously Presented) The electronic device of claim 47 wherein the electronic device is a portable personal computer.

87. (Previously Presented) The electronic device of claim 86 wherein the portable personal computer is a laptop personal computer.

88. (Previously Presented) The electronic device of claim 47 wherein the base includes the processing unit.

89. (Previously Presented) The electronic device of claim 47 further comprising the display.

90. (Previously Presented) The electronic device of claim 47 wherein a two-dimensional array of keys is disposed upon a generally planar surface of the base, and wherein the port is positioned on the generally planar surface at a position to the side of the array of keys.

91. (Previously Presented) The electronic device of claim 47 wherein a two-dimensional array of keys is disposed upon a generally planar surface of the base, and wherein the port is positioned on the generally planar surface at a position that, when the base is operatively oriented with respect to a user, is relatively distal to the user in relation to the array of keys.

In re Appln. of Higginson
Application No. 10/664,320

92. (New) The electronic device according to claim 75 wherein the port is arranged on an adapter that is releasably connectable to the base.

93. (New) An electronic device comprising:

a base;

a cursor control member including:

a housing,

an attachment element arranged at one end of the housing for detachably securing the cursor control member to the base, and

a memory; and

a port carried by the base for receiving the attachment element of the cursor control member, the port being adapted to transmit cursor control signals, corresponding to physical manipulation of the cursor control member, for directing movement of a cursor in a display when the cursor control member is engaged with the port, and wherein the port and the attachment element of the cursor control member are configured such that operatively coupling the cursor control member with the port enables a communications path for communicating information stored in the memory of the cursor control member to a processing unit via the port.

94. (New) The electronic device of claim 93 wherein the cursor control member houses mechanical and electrical components for translating the physical manipulation of the cursor control member into signals corresponding to the cursor control signals transmitted by the port.

95. (New) The electronic device of claim 94 wherein the port translates cursor control signals received from the cursor control member into the cursor control signals transmitted by the port.